



PCB LAYOUT

NOTES:

- MATERIAL:
 - HOUSING & COVER: HEMPER ATURETHERMOPLATIC WITH 30%GF, UL94V-0 COLOR: SEE NOTES 6
 - CONTACT: COPPER ALLOY
- FINISH:
 - CONTACT: GOLD PLATING(SEE TABLE)
- RECOMMENDED P.C.B THICKNESS : 1.6mm
- OTHER GENERAL SPEC. TO REFER : RJ45 SERIES SPEC.
- FOR WAVE SOLDERING LEAD-FREE PROCESS
- 10211-04310001-X X X X

R: RoHS
 COLOR:
 1: BLACK
 5: 108C
 E: 108C(FOR 智易)
 MATERIAL:
 2. PBT
 3. PA46
 PLATING:
 1. Au 1u
 2. Au 3u
 3. Au 6u

TABLE

11	10211-04310001-33ER	AU6u"	PA46	108C	RoHS
10	10211-04310001-335R	Au6u"	PA46	108C	RoHS
9	10211-04310001-331R	Au6u"	PA46	BLACK	RoHS
8	10211-04310001-325R	Au6u"	PBT	108C	RoHS
7	10211-04310001-235R	Au3u"	PA46	108C	RoHS
6	10211-04310001-22ER	Au3u"	PBT	108C	RoHS
5	10211-04310001-225R	AU3U"	PBT	108C	RoHS
4	10211-04310001-221R	Au3u"	PBT	BLACK	RoHS
3	10211-04310001-12ER	Au1u"	PBT	108C	RoHS
2	10211-04310001-125R	Au1u"	PBT	108C	RoHS
1	10211-04310001-121R	Au1u"	PBT	BLACK	RoHS
NO:	PART NO:	PLATING	MATERIAL	COLOR	ENVIRONMENTAL

COMPLIANCE WITH THE REQUIEMENT RoHS HF SONY00259 OTHER
 ※ NO USING RESTRICTED AND BANNED SUBSTANCE

3	CONTACT	SEE PART DRAWING		GOLD PLATED
2	COVER	SEE PART DRAWING	SEE PART DRAWING	UL 94V-0
1	HOUSING	SEE PART DRAWING	SEE PART DRAWING	UL 94V-0
NO:	DESCRIPTION	MATERIAL	COLOR	REMARK

CUSTOMER DRAWING		LITE Liteconn Co.,Ltd.	
-TOLERANCES- UNLESS OTHERWISE SPECIFIED		TITLE: RJ45單層單PORT10P4全塑 腳柱3.20,加強肋高0.20mm	
X.X ±0.35	X.X* ±3*	APPD:	DWG NO: 10211-04310001-XXXX
X.XX ±0.25	X.XX* ±2*	CHECK:	DATE: 2010.09.30
X.XXX ±0.15	X.XXX* ±1*	DRAW: 莊東	SCALE: 1:1
			UNIT: MM
			PAGE: 1/1